(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 29 December 2004 (29.12.2004)

PCT

(10) International Publication Number WO 2004/113634 A1

(51) International Patent Classification7: 1/58, F16S 3/06

E04B 1/24.

(21) International Application Number:

PCT/SE2004/000868

(22) International Filing Date: 4 June 2004 (04.06.2004)

(25) Filing Language:

Swedish

(26) Publication Language:

English

(30) Priority Data: 0301662-3

6 June 2003 (06.06.2003) SE

(71) Applicant and

(72) Inventor: OSSBAHR, Gilbert [SE/SE]; Föreningsgatan 49, S-582 30 Linköping (SE).

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

with international search report

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SYSTEM FOR JOINING BEAMS WITH SQUARE OR RECTANGULAR CROSS-SECTIONS



(57) Abstract: The invention constitutes of a system for detachable joining of beams with square and/or rectangular cross-section. The system comprises for respective beams, two or more fixing plates mounted in pairs on opposite sides of the beam and fixed along the beam by a friction joint maintained by tightening bolts. Respective fixing plate comprises a first surface the extension of which in at least one direction corresponds to a multiple of a beam width and a second surface turned away from the beam. The system is characterised in that two or more beams are arranged to be joined in perpendicular and/or parrallel directions by at least two opposite each other arranged fixing plates. These fixing plates are arranged to bear on each other along respective second surface. The mutual positions of the fixing plates are fixed by locking elements in through recesses in the each other facing second sides of the fixing plates. These locking elements also constitute anchoring of the tightening bolts.

